LED F313 SERIES

Ti - F313 - 22 Watts

Project: Date:

Catalog #:

Notes:

Key Features & Benefits:

- Glass-Free, Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
  - UV protected
  - Fire retardant
  - Corrosion resistant
- Ideal for Stairwells
- Zero Maintenance
- Die-Formed Heavy Gauge Steel
- Long Life:
  - 10 year warranty (12 hour run times)
  - 7 year warranty (24 hour run times)
- Safe - No Glass to Shatter
- Tamper Resistant Occupancy Sensor
- Emergency Options for Egress Requirements

10 YEAR 7 YEAR LIMITED WARRANTY NON-LIMITED WARRANTY

DLC QPL LISTED

c UL us LISTED

OCCUPANCY CAPABLE

DAMP LOCATION

DIMMABLE 0-10V

Light Specifications:

Lumen Output: Up to 2,627 Lumens
Efficacy (lm/W): Up to 124 Lumens per Watt
Kelvin: 3,000K, 3500K, 4000K, 5000K
Color Rendering Index (CRI): >82
Rated Life: >80,000 Hours

Driver Data:

Input Voltage: 120-277 VAC
Input Power: 22W
Input Current @ 120V: 0.177 Amps
Input Current @ 240V: 0.088 Amps
Input Current @ 277V: 0.076 Amps
THD: <10%
Power Factor: >0.99
Operating Temperature: -4 ~ 122°F

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-Ti-F313-S-22W-F30	22W	2,581	122	3000K	PPX81KY1
ESL-Ti-F313-S-22W-F35	22W	2,586	122	3500K	PR6JZZ5R
ESL-Ti-F313-S-22W-F40	22W	2,604	123	4000K	PMGMSWVY
ESL-Ti-F313-S-22W-F50	22W	2,627	124	5000K	PRPVXK0S

Not All Part Numbers DLC Qualified. For a Complete Listing Please Consult the DLC Qualified Products List (QPL).

Copyright © 2018 ESL Vision, LLC. All rights reserved. Rev: 10/15/2018

LED F313 SERIES

Technical Specifications

Ordering Guide:

ESL	-	Ti	-	F313	-	S	-	22W	-	F		-	
ESL		TYPE		SERIES		CLASS		WATTS		LENS	KELVIN		OPTIONS
		Ti Series		F313		S		13W (13 Watts) 15W (15 Watts) 18W (18 Watts) 22W (22 Watts)		F (Frosted)	30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)		

Example Part Number: ESL-Ti-F313-S-22W-F30

Options (Add as Suffix):

ESL-EMG-FDC-30W	Emergency Back Up, DC, 30 Watt
ESL-EMG-2DC-9W	Emergency Back Up, DC, 9 Watt, External Battery
ESL-4OCC-LDD	Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v
ESL-REM-100	Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC

Dimensions:





Copyright © 2018 ESL Vision, LLC. All rights reserved. Rev: 10/15/2018