

Product Features:

- Smallest Form Factor in Mogul-Base Category
- Integrated 4kA/4kV Surge Protection
- Step-Down Thermal Management Protection
 - Wattage step-down circuit automatically prevents overheating due to high increases in ambient temperatures. Wattage returns to normal as temperatures decrease.
- Omni-directional
- Rated for Fully Enclosed Fixtures
- Wet Location Approved
- Special Adapter Transforms Base from E26 to E39
- Direct Retrofit for HID & CFL Fixtures

Project: _____

Date: _____

Catalog #: _____

Notes: _____



SELECTABLE WATTS
12W, 18W, or 27W

Product Specifications:

Selectable Power: 12 Watts, 18 Watts, 27 Watts
 Lamp Lumen Output: Up to 3,915 Lumens
 Lamp Efficacy (lm/W): Up to 145 Lumens per Watt
 Selectable Kelvin: 3000K, 4000K, 5000K
 Dimensions:
 (E26) 2.36"Ø x 7.32"
 (EX39) 2.36"Ø x 7.36"
 CRI: >80
 Input Voltage: 120–277 VAC
 Life Span: 50,000 Hours
 Beam Angle: 300°
 Base Types:
 S-M (E26 with E39 adapter)
 EX39
 Operating Temperature: -40°F~140°F(-40°C~60°C)
 Power Factor: >0.95
 Total Harmonic Distortion (THD): < 20%



SELECTABLE KELVIN
3000K, 4000K or 5000K



WATTAGE
SELECTABLE

KELVIN
SELECTABLE

EXCLUSIVE
E39–E26 Adapter Included



No Fans



No Noise



No Bugs



Ordering Guide:

ESL	-	TYPE	-	SELECTABLE WATTAGE	-	GENERATION	-	SELECTABLE KELVIN	-	BASE
ESL	-	CL (CL) Corn Light	-	1227W 12 Watts, 18 Watts, 27 Watts	-	5 (5) 5th Generation	-	3050 3000K, 4000K, 5000K	-	VV (S-M) E26/ (EX39) EX39

Catalog Data:

ITEM#	SELECTABLE WATTAGE	MAX LUMEN OUTPUT	MAX EFFICACY (lm/W)	SELECTABLE KELVIN
ESL-CL-0918W-53050-S-M ESL-CL-0918W-53050-EX39	9W, 12W, 18W	Up to 2,615	Up to 145	3000K, 4000K, 5000K
ESL-CL-1227W-53050-S-M ESL-CL-1227W-53050-EX39	12W, 18W, 27W	Up to 3,915	Up to 145	3000K, 4000K, 5000K

Product Dimensions:

